

## Product Information

POLI-FLEX® STRETCH is a high stretchable polyurethane film with matt, reflection free surface, in accordance with Oeko-Tex Standard 100 Class I.

POLI-FLEX® STRETCH is suitable to transfer onto textiles like cotton, mixtures of polyester/cotton and polyester/acrylic.

POLI-FLEX® STRETCH can be used for lettering on T-shirts, sport & leisure wear, sport bags and promotional articles.

POLI-FLEX® STRETCH can be cut with all current plotters. We recommend using a standard 45° knife. After weeding the cut flex film is transferred by heat press. The PET liner should be removed warm. Textiles with hydrophobic impregnation are not suitable for heat transfer. In this case we recommend using POLI-FLEX® NYLON.

The soft, high stretchable transfer film offers a comfortable textile touch and convinces due to high wearing comfort. POLI-FLEX® STRETCH excels due to an excellent opacity. POLI-FLEX® STRETCH with a self-adhesive PET liner enables a reposition. The raw materials are ecologically inert, do not contain PVC, plasticizers or heavy metals.

Guarantee for a secure and long-lasting bond of POLI-FLEX® STRETCH is only given when following the specified temperature and pressure conditions.

### We recommend evaluation on test material.

Due to the various influences which occur from production and transfer of plotter letterings, consistency of the carrier materials and also washing and cleaning conditions, product liability can only cover the unprocessed material.

## Technical Data

<b>Transfer Film:</b>	Polyurethane, cast
<b>Adhesive:</b>	Polyurethane-hotmelt
<b>Thickness [mm]:</b>	0,10 +/- 5%
<b>Liner:</b>	PET-film, self-adhesive

## Transfer Conditions

<b>Temperature:</b>	160 °C
<b>Pressure:</b>	2,5 - 3,0 bar [medium pressure]
<b>Time:</b>	15 sec.

## Wash Resistance

<b>Wash resistance:</b>	80° C Suitable for tumble dry and dry-cleaning (Perchloroethylene / Tetrachloroethylene). Wash textile inside out.
-------------------------	--

## Standard Dimensions

500 mm x 10 m *
500 mm x 25 m
1.000 mm x 25 m *
1.524 mm x 25 m *

\* Non-standard dimension. Converted after order entry. Extended delivery times may occur

## Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.