



51.101N | StrongTouch

Total Mark | High Tack Printable Media

Features

51.101N | StrongTouch is a 90 micron polymeric vinyl, printable with a broad range of printing methods: (eco)solvent, UV and latex inks.

This product boosts a very high performance acrylic adhesive which allows removing the film for up to 6 months whilst maintaining the ability to stick for longer periods of time. This makes it an ideal solution for temporary floor signs and decals, or point of purchase advertising on walls and counter tops. StrongTouch will also stick to carpets with a low pile and tight pattern.

If used as a floorgraphic **we recommend to combine** the 51.101N StrongTouch **with our anti-slippery 21.000N SlipStop 100 overlaminating film.** StrongTouch can also be used to create custom whiteboard films, in combination with the Total Eraze Clear (50.000N).

Technical & Performance Information

Film Thickness	90 micron
Adhesive Thickness	25 micron
Total Thickness	115 micron
Adhesive Type	High Tack Removable Clear Solvent based Acrylic
Release Liner	140 double-sided PE coated lay-flat liner
Artificial Weathering *	5 years
Adhesion to steel (20 mins / 180°)	17 N/25mm
Adhesion to steel (24 hrs / 180°)	20 N/25mm
Dimensional Stability	Excellent
Application Temperature	+ 5 to +25 °C
Service Temperature	- 40 to +95 °C

* equivalent to vertical exposure in Mid-European climate

Certifications

Fire certification B1

Warranty

iSee2 warrants our material for one (1) year from date of shipment. The shelf life of our material is dependent on storage conditions. We recommend that the end user stores the material in the original boxes (out of direct sunlight) from our factory. We also recommend to store our material at 21°C with 50% relative humidity. iSee2 only warrants our products to be free from defects in workmanship or defects in iSee2 material. We will replace or credit any material deemed defective. No acceptance or responsibility for loss, damage or expense implied or otherwise shall be assumed by the seller or manufacturer. User assumes all risk and liability in connection herewith. All data values quoted above are typical and should not be used to deem the product defective, if measured values are different



Arkeneel 27 Tel: +31(0)318 502892
3905NS Veenendaal Fax: +31(0)318 510779
The Netherlands Email: info@signseen.nl

www.signseen.nl